

Ezo-Gum

Polyester Based Aluminum Foil Bitumen Membrane Sheet

Confirm to BS 747 : 1977 Amendment 1986 Type 5U

INTRODUCTION

Ezo-Gum is Water Proofing Aluminum Foil Bitumen Membrane on Polyester base, which being inert and inorganic, is rot proof and imparts durability and long life to the water proofing.

USES

- > Flat Roof
- > Basement & Super Structures
- > Subgrade
- > Wet Area
- > Shell Roof
- > Bath Rooms
- > Airport Run ways
- > Sealing of Roofing Flashing
- > Underpass Walls & Barrel

ADVANTAGES

- > Excellent for damp-proofing
- > High heat resistance
- > Excellent for retaining walls

TECHNICAL INFORMATION

Felt Length	10 Meter
Felt Width	1 Meter
Felt Thickness	3 MM, 4 MM
Felt Weight	35 Kg, 42 Kg

PROPERTIES

Base: Bitumen, PVC Rubber Powder, Acrylic Powder, Polyester Sheet

Thermal Insulation: Reflex up 70% Reflexion and will preserve over Heating.

APPLICATION METHOD

Water Proofing with Ezo-Gum

- > Firstly cleaning the surface with **coconut brush**.
- > Sticking Coat of Primer (.5 kg in M²)
- > Torch apply Bitumen Membrane Sheet with 75 mm Overlap

BENEFITS

- # Ezo-Gum is Aluminum Foil Bitumen Membrane Sheet water proofing is **40 % LESS** in cost as compared by Chemicals.
- # Ezo-Gum (Raw Material is imported)
- # There will be no **MELTING** found in extreme temperature of **80 Degree Centigrade** in Summer Season up to **Minus 0** temperature because it is more Flexible then any material.

M/s Ghausia Traders
M.A Butt and Sons

GHAUSIA

Building Protection Products

Tell: 92+42+35 50 37 05

Cell: 92+33+41 56 81 58

E-mail: ghausia_products786@yahoo.com

Scraping & Cleaning



Primer Coat



Membrane Fixing



Final

