

GRIP BOND.32

Engineering Product EPDM to Concrete Bonding Adhesives

Description

The Bond.32 is a Single component Bonding agent,.
The Bond Adhesive also Ideal for bonding Leather, Rubber,
Textiles, Wood, Glass, Concrete and a number of Metals .
A reliable and general purpose EPDM to Concrete adhesive
giving a tough, resilient and heat resistant bond.

ADVANTAGES

- > Easy to apply
- > Unaffected by moisture
- > Highly effective , even on damp surfaces
- > Workable at low temperatures
- > High tensile strength

BENIFITES

- > Excellent for roof water proofing
- > Excellent for basement water proofing
- > Excellent for under pass & Fly overs
- > Excellent for airports

TECHNICAL INFORMATION

Colour	Gray
Solids (%)	49.0-52.5%
Specific gravity	1.0
Viscosity (cp)	16000-20000

APPLICATION

- > The Substrate must be clean, dry, smooth and free of any foreign materials, grease or oil.
- > Apply an even, heavy coat of .5 mm thick medium-naproller or brush.
- > Do not allow Grip Bond.32 in the lap area.
- > 100 % coverage is required .

PACKING

4-ltr Tin, 20-ltr Pail, 30-ltr Can.

COVERAGE

½ -ltr Per M²

CONTACT DETAILS

M/s Ghausia Building Protection Products

Tell:0423-550 37 05,Cell:0334-1568158

E-mail: ghausia_products786@yahoo.com

