

Hot Rubberized Bitumen (HRB.01)

GENERAL

HRB.01 Hot-Applied Rubberized Waterproofing Bitumen is a hot-applied asphalt-based composition which is specifically formulated as a fluid material which is applied to form a continuous adhered waterproofing system.

USES

HRB.01 Hot-Applied Rubberized Waterproofing Bitumen is generally used in the waterproofing of various types of Portland cement concrete surfaces including precast and poured in place

- **Roof**
- **Basement**
- **Under Pass Wall & Bed**
- **Flyovers Piling**
- **Bridge Decks**
- **Tunnels**
- **Concrete Foundations**
- **Parking Structures.**

The unique properties of the Bitumen permit its use in **re-roofing** operations over a variety of substrates, and for waterproofing of other surfaces including gypsum and wood surfaces. Since Hot-Applied Rubberized Waterproofing Bitumen is designed as a **flexible, elastomeric waterproofing material**, applications are normally protected from traffic loadings, abrasion, puncturing, and U.V. radiation with appropriate surface coverings for the specific use.

Application

Verify proper product selection, heating methods, surface preparation requirements, application geometrics and usage and safety precautions. These instructions are provided with each product. Firstly cleaning surface with wire brush, coconut brush or air blower, then applying the HRB.01 with **Viper or roller**,

Specification

HRB.01 Hot-Applied Rubberized Waterproofing Membrane meets all requirements of Canadian General Standards Board. **HRB.01 Coverage 1 kg/M²**

Packing

4 kg Galen, 15 kg Tin, 250 kg Drum